

Package ‘ROC’

September 23, 2024

Version 1.80.0

Title utilities for ROC, with microarray focus

Author Vince Carey <stvjc@channing.harvard.edu>, Henning Redestig for
C++ language enhancements

Maintainer Vince Carey <stvjc@channing.harvard.edu>

Description Provide utilities for ROC, with microarray focus.

Depends R (>= 1.9.0), utils, methods

Imports knitr

Suggests rmarkdown, Biobase, BiocStyle

License Artistic-2.0

URL <http://www.bioconductor.org>

LazyLoad Yes

biocViews DifferentialExpression

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/ROC>

git_branch RELEASE_3_19

git_last_commit 5cc6651

git_last_commit_date 2024-04-30

Repository Bioconductor 3.19

Date/Publication 2024-09-22

Contents

| | |
|------------------------|----------|
| AUC | 2 |
| plot-methods | 3 |
| rocc-class | 4 |
| rocdemo.sca | 5 |
| trapezint | 6 |
| Index | 8 |

AUC

functionals of ROC curve

Description

various functionals of ROC (Receiver Operating Characteristic) curves

Usage

```
AUC(rocobj)
AUCi(rocobj)
pAUC(rocobj, t0)
pAUCi(rocobj, t0)
```

Arguments

| | |
|--------|---|
| rocobj | element of class rocc |
| t0 | FPR point at which TPR is evaluated or limit in (0,1) to integrate to |

Details

AUC, pAUC, AUCi and pAUCi compute the Area Under the Curve.

AUC and pAUC employ the trapezoidal rule. AUCi and pAUCi use integrate().

AUC and AUCi compute the area under the curve from 0 to 1 on the x-axis (i.e., the 1 - specificity axis).

pAUC and pAUCi compute the area under the curve from 0 to argument t0 on the x-axis (i.e., the 1 - specificity axis).

Elements of class rocc can be created by rocdemo.sca() or other constructors you might make using the code of rocdemo.sca() as a template.

Author(s)

Vince Carey (stvjc@channing.harvard.edu)

References

Rosner, B., 2000, *Fundamentals of Biostatistics, 5th Ed.*, pp. 63–65

Duda, R. O., Hart, P. E., Stork, D. G., 2001 *Pattern Classification, 2nd Ed.*, p. 49

See Also

rocdemo.sca

Examples

```

set.seed(123)
R1 <- rocdemo.sca( rbinom(40,1,.3), rnorm(40), dxrule.sca,
  caseLabel="new case", markerLabel="demo Marker" )
print(AUC(R1))
print(pAUC(R1,.3))
print(pAUCi(R1,.3))
print(ROC(R1,.3))

```

plot-methods

plot method for ROC curves

Description

plot method for ROC curves

Methods

x = rocc plots an ROC curve object, with additional parameters available:

show.thresh (logical): should marker threshold values be plotted?

jit (logical): should plotted points be jittered?

add (logical): increment to current plot?

line (logical): plot points or lines?

threshCex (numeric): if showing threshold values, set character expansion in text call to this value

threshYsh (numeric): if showing threshold values, add this quantity to y coordinate of curve to plot the threshold value (should be negative for printing below point)

threshDig (numeric): if showing threshold values, use this as the digits parameter to round to display the threshold

... extra parameters passed to base plot, lines or points as needed

Examples

```

set.seed(123)
R1 <- rocdemo.sca( rbinom(40,1,.3), rnorm(40), dxrule.sca,
  caseLabel="new case", markerLabel="demo Marker" )
plot(R1, line=TRUE, show.thresh=TRUE, lwd=2, threshDig=2)
R2 <- rocdemo.sca( rbinom(40,1,.3), rnorm(40), dxrule.sca,
  caseLabel="new case", markerLabel="demo Marker" )
plot(R2, line=TRUE, add=TRUE, col="green", lwd=2 )
R3 <- rocdemo.sca( rbinom(40,1,.4), rnorm(40), dxrule.sca,
  caseLabel="new case", markerLabel="demo Marker" )
points(R3, col="red", pch=19)

```

| | |
|------------|---|
| rocc-class | <i>Class rocc, ROC curve representation</i> |
|------------|---|

Description

object representing ROC curve, typically created using rocdemo.sca

Creating Objects

```
new('rocc',  
  sens = ..., # Object of class numeric  
  spec = ..., # Object of class numeric  
  rule = ..., # Object of class function  
  cuts = ..., # Object of class numeric  
  markerLabel = ..., # Object of class character  
  caseLabel = ..., # Object of class character  
)
```

Slots

sens: Object of class "numeric" sensitivity values
spec: Object of class "numeric" specificity values
rule: Object of class "function" rule to classify objects
cuts: Object of class "numeric" thresholds defining curve
markerLabel: Object of class "character" name of measured marker
caseLabel: Object of class "character" name of condition

Methods

plot (rocc, missing): a plotting function with some additional parameters

Examples

```
set.seed(123)  
R1 <- rocdemo.sca( rbinom(40,1,.3), rnorm(40), dxrule.sca,  
  caseLabel="new case", markerLabel="demo Marker" )  
plot( R1, show.thresh=TRUE )
```

rocdemo.sca *function to build objects of class 'rocc'*

Description

rocdemo.sca – demonstrate 'rocc' class construction using a scalar marker and simple functional rule

Usage

```
rocdemo.sca(truth, data, rule=NULL,
            cutpts=NA,
            markerLabel="unnamed marker", caseLabel="unnamed diagnosis",
            quiet=TRUE)
```

Arguments

| | |
|-------------|--|
| truth | true classification of objects. Must take values 0 or 1. |
| data | quantitative markers used to classify |
| rule | rule: a function with arguments (x, thresh) returning 0 or 1. If no rule is provided or the standard rule <code>dxrule.sca</code> is passed, a faster C-based implementation is used to compute sensitivity and specificity. |
| cutpts | values of thresholds; no NA allowed, or they will be recomputed using smallest gap between data points with distinct values |
| markerLabel | textual label describing marker |
| caseLabel | textual label describing classification |
| quiet | defaults to TRUE, suppressing message about discovery of NA in cutpts |

Details

`dxrule.sca` is function (x, thresh) `ifelse(x > thresh, 1, 0)`

The default value of argument `cutpts` is a point less than `min(data)`, points separating the unique values of data and a point greater than `max(data)`.

Value

an object of S4 class `rocc`

Author(s)

Vince Carey (stvjc@channing.harvard.edu)

See Also

AUC

Examples

```

set.seed(123)
R1 <- rocdemo.sca( rbinom(40,1,.3), rnorm(40), caseLabel="new case", markerLabel="demo Marker" )
plot(R1, line=TRUE, show.thresh=TRUE)

truth <- c(0, 1, 0, 1, 1, 0, 1, 1)
data <- c(2, 3, 4, 4, 5, 6, 7, 8)
R2 <- rocdemo.sca(truth, data, dxrule.sca)
plot(R2, line=TRUE, show.thresh=TRUE)
R3 <- rocdemo.sca(truth, data, function(x, thresh) 1 - dxrule.sca(x, thresh))
if (AUC(R2) + AUC(R3) != 1) stop('Sum of AUCs should be 1.')
#
# more involved
#
set.seed(1234)
x = runif(1000)
w = runif(1000)
z = rbinom(1000, 1, plogis(-2.7+6.2*x + .3*w))
m1 = glm(z~x, fam=binomial)
demorule.glm.clo = function(model) function(w,thresh)
  ifelse(predict(model, newdata=list(x=w), type="response")>thresh, 1, 0)
demorule.glm = demorule.glm.clo(m1)
R4 = rocdemo.sca(z, x, demorule.glm )
plot(R4)

```

trapezint

trapezoidal rule for AUC

Description

trapezoidal rule for AUC

Usage

```
trapezint(x, y, a, b)
```

Arguments

| | |
|---|--------------------------------|
| x | x - abscissae |
| y | y - ordinates |
| a | a - lower limit of integration |
| b | b - upper limit of integration |

Details

uses approx

trapezint

7

Value

estimated AUC

Examples

```
x <- sort(runif(30))
y <- sin(x)
print(trapezint(x,y,0,1))
```

Index

* **methods**

plot-methods, 3

rocc-class, 4

* **models**

AUC, 2

rocdemo.sca, 5

trapezint, 6

.initClasses (rocc-class), 4

AUC, 2

AUCi (AUC), 2

dxrule.sca (rocdemo.sca), 5

lines, rocc-method (plot-methods), 3

pAUC (AUC), 2

pAUCi (AUC), 2

plot, rocc-method (plot-methods), 3

plot-methods, 3

points, rocc-method (plot-methods), 3

ROC (AUC), 2

rocc-class, 4

rocdemo.sca, 5

trapezint, 6