

Package ‘UNDO’

November 15, 2024

Type Package

Title Unsupervised Deconvolution of Tumor-Stromal Mixed Expressions

Version 1.48.0

Date 2014-07-17

Author Niya Wang <wangny@vt.edu>

Maintainer Niya Wang <wangny@vt.edu>

Depends R (>= 2.15.2), methods, BiocGenerics, Biobase

Imports MASS, boot, nnl, stats, utils

biocViews Software

Description UNDO is an R package for unsupervised deconvolution of tumor and stromal mixed expression data. It detects marker genes and deconvolutes the mixing expression data without any prior knowledge.

License GPL-2

git_url <https://git.bioconductor.org/packages/UNDO>

git_branch RELEASE_3_20

git_last_commit 353461e

git_last_commit_date 2024-10-29

Repository Bioconductor 3.20

Date/Publication 2024-11-14

Contents

| | |
|-------------------------------------|---|
| UNDO-package | 2 |
| BiologicalMixMCF7HS27 | 2 |
| calc_E1 | 3 |
| dimension_reduction | 4 |
| gene_expression_input | 5 |
| marker_gene_selection | 5 |
| mixing_matrix_computation | 6 |
| NumericalMixingMatrix | 7 |
| NumericalMixMCF7HS27 | 7 |
| PureMCF7HS27 | 8 |
| two_source_deconv | 9 |

| | |
|--------------|-----------|
| Index | 11 |
|--------------|-----------|

UNDO-package *Implementation of UNDO (unsupervised deconvolution of tumor-stromal mixed expressions)*

Description

This package contains main function "two_source_deconv" to implement the deconvolution of mixed tumor-stromal expressions in a completely unsupervised way. The prior knowledge of mixing matrix or pure expression is not needed. The package detects marker genes and calculate the mixing matrix and pure expressions automatically.

Details

Package: UNDO
Type: Package
Version: 1.7.3
Date: 2014-04-30
License: GPL version 2 or later

```
two_source_deconv(ExpressionData,lowerper=0.4,highper=0.1,epsilon1=0.01,epsilon2=0.01,A=NULL,S1=NULL,S2=N
```

Author(s)

Niya Wang <wangny@vt.edu>

Examples

```
data(NumericalMixMCF7HS27)
X <- NumericalMixMCF7HS27
deconvResult <- two_source_deconv(X, lowerper = 0.4, highper = 0.1, epsilon1 = 0.1, epsilon2 = 0.1, A = NULL, S1=N
```

BiologicalMixMCF7HS27 *MCF7 and HS27 biologically mixed*

Description

Expression data from MCF7 and HS27 biologically mixing

Usage

```
data(BiologicalMixMCF7HS27)
```

Format

The format is: Formal class 'ExpressionSet' [package "Biobase"] with 7 slots ..@ experimentData :Formal class 'MIAME' [package "Biobase"] with 13 slots ..@ name : chr "" ..@ lab : chr "" ..@ contact : chr "" ..@ title : chr "" ..@ abstract : chr "" ..@ url : chr "" ..@ pubMedIds : chr "" ..@ samples : list() ..@ hybridizations : list() ..@ normControls : list() ..@ preprocessing : list() ..@ other : list() ..@ .__classVersion__:Formal class 'Versions' [package "Biobase"] with 1 slots ..@ .Data:List of 2 ..@ .\$. : int [1:3] 1 0 0 ..@ .\$. : int [1:3] 1 1 0 ..@ assayData :<environment: 0x0000000008d92618> ..@ phenoData :Formal class 'AnnotatedDataFrame' [package "Biobase"] with 4 slots ..@ varMetadata :'data.frame': 0 obs. of 1 variable: ..@ labelDescription: chr(0) ..@ data :'data.frame': 2 obs. of 0 variables ..@ dimLabels : chr [1:2] "sampleNames" "sampleColumns" ..@ .__classVersion__:Formal class 'Versions' [package "Biobase"] with 1 slots ..@ .Data:List of 1 ..@ .\$. : int [1:3] 1 1 0 ..@ featureData :Formal class 'AnnotatedDataFrame' [package "Biobase"] with 4 slots ..@ varMetadata :'data.frame': 0 obs. of 1 variable: ..@ labelDescription: chr(0) ..@ data :'data.frame': 22215 obs. of 0 variables ..@ dimLabels : chr [1:2] "featureNames" "featureColumns" ..@ .__classVersion__:Formal class 'Versions' [package "Biobase"] with 1 slots ..@ .Data:List of 1 ..@ .\$. : int [1:3] 1 1 0 ..@ annotation : chr "HG-U133A" ..@ protocolData :Formal class 'AnnotatedDataFrame' [package "Biobase"] with 4 slots ..@ varMetadata :'data.frame': 0 obs. of 1 variable: ..@ labelDescription: chr(0) ..@ data :'data.frame': 2 obs. of 0 variables ..@ dimLabels : chr [1:2] "sampleNames" "sampleColumns" ..@ .__classVersion__:Formal class 'Versions' [package "Biobase"] with 1 slots ..@ .Data:List of 1 ..@ .\$. : int [1:3] 1 1 0 ..@ .__classVersion__:Formal class 'Versions' [package "Biobase"] with 1 slots ..@ .Data:List of 4 ..@ .\$. : int [1:3] 3 1 0 ..@ .\$. : int [1:3] 2 23 6 ..@ .\$. : int [1:3] 1 3 0 ..@ .\$. : int [1:3] 1 0 0

Examples

```
data(BiologicalMixMCF7HS27)
str(BiologicalMixMCF7HS27)
```

calc_E1

function calculating the E1 measurement

Description

A function used to calculate the E1 measurement when the real mixing matrix is provided

Usage

```
calc_E1(A, Aest)
```

Arguments

| | |
|------|-------------------------|
| A | real mixing matrix |
| Aest | estimated mixing matrix |

Value

E1 measurement (numeric)

Author(s)

Niya Wang <wangny@vt.edu>

Examples

```
A <- matrix(runif(4),2,2)
Aest <- matrix(runif(4),2,2)
E1 <- calc_E1(A,Aest) # to calculate the similarity of two random 2*2 matrix
```

dimension_reduction *Dimension reduction function*

Description

When the number of input samples is larger than 2, this function is called to reduce the dimension to 2 by using PCA.

Usage

```
dimension_reduction(X)
```

Arguments

X gene expression data matrix

Value

X
dimenMatrix the dimension reduction matrix used to recover the mixing matrix for all the samples

Author(s)

Niya Wang (wangny@vt.edu)

Examples

```
X <- matrix(runif(5000),1000,5)
dimenResult <- dimension_reduction(X)
```

gene_expression_input *Detect whether the input gene expression data are valid*

Description

Check the input gene expression data to see whether they are nonempty, nonnegative, etc.

Usage

```
gene_expression_input(X)
```

Arguments

X gene expression data matrix with row representing genes/probe sets, and column representing samples.

Value

If the input is valid, the output will be the same as the input; otherwise, if the input contains NA, the corresponding rows will be deleted. if the input contains negative value, the algorithm will stop and give error information.

Author(s)

Niya Wang (wangny@vt.edu)

Examples

```
gene_expression <- matrix(runif(2000),1000,2)
valid_gene_expression <- gene_expression_input(gene_expression)
```

marker_gene_selection *Select marker genes in two sources*

Description

Select the marker genes in tumor and stroma in an unsupervised way

Usage

```
marker_gene_selection(X, lower, higher, epsilon1, epsilon2)
```

Arguments

| | |
|----------|---|
| X | gene expression data |
| lower | The percentage of genes the user wants to remove with lowest norm. The range should be between 0 and 1. |
| higher | The percentage of genes the user wants to remove with highest norm. The range should be between 0 and 1. |
| epsilon1 | Influence the number of marker genes. With increasing of epsilon1, the number marker genes in source 1 will increase. The value should be positive. |
| epsilon2 | Influence the number of marker genes. With increasing of epsilon1, the number marker genes in source 2 will increase. The value should be positive. |

Value

| | |
|-------------|---|
| a1 | The slope of marker genes in source 1 |
| a2 | The slope of marker genes in source 2 |
| MG1 | The gene list of marker genes in source 1 |
| MG2 | The gene list of marker genes in source 2 |
| dimenMatrix | dimension reduction matrix |

Author(s)

Niya Wang (wangny@vt.edu)

Examples

```
X <- matrix(runif(20000),10000,2)
MG_set <- marker_gene_selection(X, 0.4, 0.1, 0.1, 0.1)
```

mixing_matrix_computation

Calculate and scale the mixing matrix

Description

Calculate the mixing matrix based on the output from `marker_gene_selection()`, and scale the mixing matrix to make the sum of proportions from tumor and stroma equal to 1. The pure expression levels of tumor and stroma are also computed.

Usage

```
mixing_matrix_computation(X, a1, a2, dimenMatrix)
```

Arguments

| | |
|-------------|--|
| X | Gene expression data matrix |
| a1 | The slope of marker genes in source 1 |
| a2 | The slope of marker genes in source 2 |
| dimenMatrix | The dimension reduction matrix used to recover mixing matrix for all the samples |

Value

Aest estimated mixing matrix
Sest estimated pure gene expression of two sources

Author(s)

Niya Wang (wangny@vt.edu)

Examples

```
a1<- matrix(runif(2),2,1)
a2<- matrix(runif(2),2,1)
X <- 1000*matrix(runif(20000),10000,2)
dimenMatrix <- NULL
Deconv <- mixing_matrix_computation(X, a1, a2, dimenMatrix)
```

NumericalMixingMatrix *mixing matrix of data NumericalMixMCF7HS27*

Description

real mixing matrix of data NumericalMixMCF7HS27

Usage

```
data(NumericalMixingMatrix)
```

Format

The format is: num [1:2, 1:2] 0.775 0.15 0.225 0.85 - attr(*, "dimnames")=List of 2 ..\$: NULL ..\$: chr [1:2] "V1" "V2"

Examples

```
data(NumericalMixingMatrix)
str(NumericalMixingMatrix)
```

NumericalMixMCF7HS27 *MCF7 and HS27 numerically mixed*

Description

Expression data from MCF7 and HS27 numerically mixing

Usage

```
data(NumericalMixMCF7HS27)
```

Format

The format is: Formal class 'ExpressionSet' [package "Biobase"] with 7 slots ..@ experimentData :Formal class 'MIAME' [package "Biobase"] with 13 slots ..@ name : chr "" ..@ lab : chr "" ..@ contact : chr "" ..@ title : chr "" ..@ abstract : chr "" ..@ url : chr "" ..@ pubMedIds : chr "" ..@ samples : list() ..@ hybridizations : list() ..@ normControls : list() ..@ preprocessing : list() ..@ other : list() ..@ __classVersion__:Formal class 'Versions' [package "Biobase"] with 1 slots ..@ .Data:List of 2 ..@ : int [1:3] 1 0 0 ..@ : int [1:3] 1 1 0 ..@ assayData :<environment: 0x00000000e86a5d0> ..@ phenoData :Formal class 'AnnotatedDataFrame' [package "Biobase"] with 4 slots ..@ varMetadata :'data.frame': 0 obs. of 1 variable: ..@ labelDescription: chr(0) ..@ data :'data.frame': 2 obs. of 0 variables ..@ dimLabels : chr [1:2] "sampleNames" "sampleColumns" ..@ __classVersion__:Formal class 'Versions' [package "Biobase"] with 1 slots ..@ .Data:List of 1 ..@ : int [1:3] 1 1 0 ..@ featureData :Formal class 'AnnotatedDataFrame' [package "Biobase"] with 4 slots ..@ varMetadata :'data.frame': 0 obs. of 1 variable: ..@ labelDescription: chr(0) ..@ data :'data.frame': 22215 obs. of 0 variables ..@ dimLabels : chr [1:2] "featureNames" "featureColumns" ..@ __classVersion__:Formal class 'Versions' [package "Biobase"] with 1 slots ..@ .Data:List of 1 ..@ : int [1:3] 1 1 0 ..@ annotation : chr "HG-U133A" ..@ protocolData :Formal class 'AnnotatedDataFrame' [package "Biobase"] with 4 slots ..@ varMetadata :'data.frame': 0 obs. of 1 variable: ..@ labelDescription: chr(0) ..@ data :'data.frame': 2 obs. of 0 variables ..@ dimLabels : chr [1:2] "sampleNames" "sampleColumns" ..@ __classVersion__:Formal class 'Versions' [package "Biobase"] with 1 slots ..@ .Data:List of 1 ..@ : int [1:3] 1 1 0 ..@ __classVersion__:Formal class 'Versions' [package "Biobase"] with 1 slots ..@ .Data:List of 4 ..@ : int [1:3] 3 1 0 ..@ : int [1:3] 2 23 6 ..@ : int [1:3] 1 3 0 ..@ : int [1:3] 1 0 0

Examples

```
data(NumericalMixMCF7HS27)
str(NumericalMixMCF7HS27)
```

PureMCF7HS27

pure MCF7 and HS27

Description

pure MCF7 and HS27 expression data

Usage

```
data(PureMCF7HS27)
```

Format

The format is: Formal class 'ExpressionSet' [package "Biobase"] with 7 slots ..@ experimentData :Formal class 'MIAME' [package "Biobase"] with 13 slots ..@ name : chr "" ..@ lab : chr "" ..@ contact : chr "" ..@ title : chr "" ..@ abstract : chr "" ..@ url : chr "" ..@ pubMedIds : chr "" ..@ samples : list() ..@ hybridizations : list() ..@ normControls : list() ..@ preprocessing : list() ..@ other : list() ..@ __classVersion__:Formal class 'Versions' [package "Biobase"] with 1 slots ..@ .Data:List of 2 ..@ : int [1:3] 1 0 0 ..@ : int [1:3] 1 1 0 ..@ assayData :<environment: 0x00000000e979d20>

```

..@ phenoData :Formal class 'AnnotatedDataFrame' [package "Biobase"] with 4 slots .. ..@
varMetadata :'data.frame': 0 obs. of 1 variable: .. .. $ labelDescription: chr(0) .. ..@ data
:'data.frame': 2 obs. of 0 variables .. ..@ dimLabels : chr [1:2] "sampleNames" "sampleColumns"
.. ..@ .__classVersion__:Formal class 'Versions' [package "Biobase"] with 1 slots .. ..@
.Data:List of 1 .. .. $ : int [1:3] 1 1 0 ..@ featureData :Formal class 'AnnotatedDataFrame'
[package "Biobase"] with 4 slots .. ..@ varMetadata :'data.frame': 0 obs. of 1 variable: .. ..
.. $ labelDescription: chr(0) .. ..@ data :'data.frame': 22215 obs. of 0 variables .. ..@
dimLabels : chr [1:2] "featureNames" "featureColumns" .. ..@ .__classVersion__:Formal class
'Versions' [package "Biobase"] with 1 slots .. ..@ .Data:List of 1 .. .. $ : int [1:3]
1 1 0 ..@ annotation : chr "HG-U133A" ..@ protocolData :Formal class 'AnnotatedDataFrame'
[package "Biobase"] with 4 slots .. ..@ varMetadata :'data.frame': 0 obs. of 1 variable: .. ..
.. $ labelDescription: chr(0) .. ..@ data :'data.frame': 2 obs. of 0 variables .. ..@ dimLabels
: chr [1:2] "sampleNames" "sampleColumns" .. ..@ .__classVersion__:Formal class 'Versions'
[package "Biobase"] with 1 slots .. ..@ .Data:List of 1 .. .. $ : int [1:3] 1 1 0 ..@
.__classVersion__:Formal class 'Versions' [package "Biobase"] with 1 slots .. ..@ .Data:List of 4
.. .. $ : int [1:3] 3 1 0 .. .. $ : int [1:3] 2 23 6 .. .. $ : int [1:3] 1 3 0 .. .. $ : int [1:3] 1 0
0

```

Examples

```

data(PureMCF7HS27)
str(PureMCF7HS27)

```

| | |
|-------------------|--|
| two_source_deconv | <i>Main function to call other subfunction to deconvolute the mixed expression data.</i> |
|-------------------|--|

Description

This is the main function that is to call all the other subfunctions and realize the deconvolution of mixed expression data. When the real mixing matrix exist, it will also compare the estimated mixing matrix and real mixing matrix and give the E1 measurement.

Usage

```
two_source_deconv(ExpressionData, lower = 0.4, higher = 0.1, epsilon1 = 0.01, epsilon2 = 0.01, A =
```

Arguments

| | |
|----------------|---|
| ExpressionData | gene expression data matrix/ExpressionSet object |
| lower | The percentage of genes the user wants to remove with lowest norm. The range should be between 0 and 1. |
| higher | The percentage of genes the user wants to remove with highest norm. The range should be between 0 and 1. |
| epsilon1 | Influence the number of marker genes. With increasing of epsilon1, the number marker genes in source 1 will increase. The value should be positive. |
| epsilon2 | Influence the number of marker genes. With increasing of epsilon1, the number marker genes in source 2 will increase. The value should be positive. |
| A | real mixing matrix if existing |
| S1 | Pure expression profile of first source if existing |
| S2 | Pure expression profile of second source if existing |
| return | if it is equal to 0, do not return estimated S; otherwise, return the estimated S. |

Value

| | |
|------|---|
| Aest | estimated mixing matrix |
| E1 | E1 measurement between real and estimated mixing matrix |

Author(s)

Niya Wang (wangny@vt.edu)

Examples

```
data(NumericalMixMCF7HS27)
X <- NumericalMixMCF7HS27
deconvResult <- two_source_deconv(X, lowper = 0.4, highper = 0.1, epsilon1 = 0.1, epsilon2 = 0.1, A = NULL, S1=N
```

Index

* datasets

BiologicalMixMCF7HS27, [2](#)
NumericalMixingMatrix, [7](#)
NumericalMixMCF7HS27, [7](#)
PureMCF7HS27, [8](#)

* methods

UNDO-package, [2](#)

* package

UNDO-package, [2](#)

BiologicalMixMCF7HS27, [2](#)

calc_E1, [3](#)

dimension_reduction, [4](#)

gene_expression_input, [5](#)

marker_gene_selection, [5](#)

mixing_matrix_computation, [6](#)

NumericalMixingMatrix, [7](#)

NumericalMixMCF7HS27, [7](#)

PureMCF7HS27, [8](#)

two_source_deconv, [9](#)

UNDO (UNDO-package), [2](#)

UNDO-package, [2](#)