

Package ‘apeglm’

November 14, 2024

Title Approximate posterior estimation for GLM coefficients

Version 1.28.0

Maintainer Anqi Zhu <anqizhu@live.unc.edu>

Description apeglm provides Bayesian shrinkage estimators for effect sizes for a variety of GLM models, using approximation of the posterior for individual coefficients.

VignetteBuilder knitr, rmarkdown

Imports emdbook, SummarizedExperiment, GenomicRanges, methods, stats, utils, Rcpp

Suggests DESeq2, airway, knitr, rmarkdown, testthat

LinkingTo Rcpp, RcppEigen, RcppNumerical

License GPL-2

Encoding UTF-8

LazyData true

biocViews ImmunoOncology, Sequencing, RNASeq, DifferentialExpression, GeneExpression, Bayesian

RoxygenNote 7.1.1

git_url <https://git.bioconductor.org/packages/apeglm>

git_branch RELEASE_3_20

git_last_commit e8962a4

git_last_commit_date 2024-10-29

Repository Bioconductor 3.20

Date/Publication 2024-11-14

Author Anqi Zhu [aut, cre],
Joshua Zitovsky [ctb],
Joseph Ibrahim [aut],
Michael Love [aut]

Contents

| | |
|---------------------|---|
| apeglm | 2 |
| bbEstDisp | 6 |
| logLikNB | 7 |
| svalue | 8 |

| | |
|--------------|----------|
| Index | 9 |
|--------------|----------|

Description

apeglm provides Bayesian shrinkage estimators for effect sizes in GLM models, using approximation of the posterior for individual coefficients.

Usage

```
apeglm(
  Y,
  x,
  log.lik,
  param = NULL,
  coef = NULL,
  mle = NULL,
  no.shrink = FALSE,
  interval.type = c("laplace", "HPD", "credible"),
  interval.level = 0.95,
  threshold = NULL,
  contrasts,
  weights = NULL,
  offset = NULL,
  flip.sign = TRUE,
  prior.control,
  multiplier = 1,
  ngrid = 50,
  nsd = 5,
  ngrid.nuis = 5,
  nsd.nuis = 2,
  log.link = TRUE,
  param.sd = NULL,
  method = c("general", "nbinomR", "nbinomCR", "nbinomC", "nbinomC*", "betabinR",
    "betabinCR", "betabinC", "betabinC*"),
  optim.method = "BFGS",
  bounds = c(-Inf, Inf)
)
```

Arguments

- | | |
|---------|--|
| Y | the observations, which can be a matrix or SummarizedExperiment, with columns for samples and rows for "features" (e.g. genes in a genomic context). If Y is a SummarizedExperiment, apeglm will return, in addition to other list items, a GRanges or GRangesList ranges with the estimated coefficients as metadata columns. |
| x | design matrix, with intercept in the first column. Continuous-valued columns should be centered and scaled to unit variance, or at least set so that the scale (in SD) is not very large or very small |
| log.lik | the log of likelihood function, specified by the user. For Negative Binomial distribution, user can use logLikNB provided within the package. |

| | |
|----------------|---|
| param | the other parameter(s) to be used in the likelihood function, e.g. the dispersion parameter for a negative binomial distribution. this can be a vector or a matrix (with columns as parameters) |
| coef | (optional) the index of the coefficient for which to generate posterior estimates (FSR, svalue, and intervals) |
| mle | (optional) a 2 column matrix giving the MLE and its standard error of coef. this will be used to adapt the scale of the prior (empirical Bayes). This overrides the prior.scale specified by prior.control and sets no.shrink to all coefficients other than coef. Note that these MLE's and SE's should be on the natural log scale for a log link GLM. |
| no.shrink | logical, if TRUE, apeglm won't perform shrinkage (default is FALSE) |
| interval.type | (optional) can be "laplace", "HPD", or "credible", which specifies the type of Bayesian interval that the user wants to output; "laplace" represents the Laplace approximation of the posterior mode |
| interval.level | (optional) default is 0.95 |
| threshold | (optional) a threshold for integrating posterior probabilities, see details under 'Value'. Note that this should be on the natural log scale for a log link GLM. |
| contrasts | (optional) contrast matrix, same number of rows as x |
| weights | (optional) weights matrix, same shape as Y |
| offset | (optional) offsets matrix, same shape as Y. Note that this should be on the natural log scale for a log link GLM. |
| flip.sign | whether to flip the sign of threshold value when MAP is negative, default is TRUE (threshold must then be positive) |
| prior.control | see Details |
| multiplier | a positive number, when the prior is adapted to the mle matrix provided, this parameter connects the scale of the estimated distribution of betas to the scale of the prior. the default value was chosen based on FSR and error analysis of simulated data |
| ngrid | the number of grid points for grid integration of intervals |
| nsd | the number of SDs of the Laplace posterior approximation to set the left and right edges of the grid around the MAP |
| ngrid.nuis | the number of grid points for nuisance parameters |
| nsd.nuis | the number of Laplace standard errors to set the left and right edges of the grid around the MAP of the nuisance parameters |
| log.link | whether the GLM has a log link (default = TRUE) |
| param.sd | (optional) potential uncertainty measure on the parameter param. this should only be a vector, used when param specifies a single parameter |
| method | options for how apeglm will find the posterior mode and SD. The default is "general" which allows the user to specify a likelihood in a general way. Alternatives for faster performance with the Negative Binomial likelihood are: "nbinomR", "nbinomCR", and "nbinomC" / "nbinomC*" These alternative methods should provide increasing speeds, respectively. (Also for beta binomial, substitute "betabin" for "nbinom" in the above.) From testing on RNA-seq data, the nbinom methods are roughly 5x, 10x and 50x faster than "general". Note that "nbinomC" uses C++ to find the MAP for the coefficients, but does not calculate or return the posterior SD or other quantities. "nbinomC*" is the same as "nbinomC", but includes a random start for finding the MAP. "nbinomCR" uses |

C++ to calculate the MAP and then estimates the posterior SD in R, with the exception that if the MAP from C++ did not converge or gives negative estimates of posterior variance, then this row is refit using optimization in R. These alternatives require the degrees of freedom for the prior distribution to be 1, and will ignore any function provided to the `log.lik` argument. `param` should specify the dispersion parameter of a Negative Binomial (such that $\text{Var} = \mu + \text{param} \mu^2$).

`optim.method` the method passed to `optim`
`bounds` the bounds for the numeric optimization

Details

`prior.control` is a list of parameters that will be passed to determine the prior distribution. Users are allowed to have a Normal prior on the intercept, and a `t` prior on the non-intercept coefficients (similar to `bayesglm` in the `arm` package. The following are defaults:

- `no.shrink = 1`: index of the coefficient(s) not to shrink
- `prior.mean = 0`: mean of `t` prior
- `prior.scale = 1`: scale of `t` prior
- `prior.df = 1`: df of `t` prior
- `prior.no.shrink.mean = 0`: mean of Normal
- `prior.no.shrink.scale = 15`: scale of Normal

So without specifying `prior.control`, the following is set inside `apeglm`:

```
prior.control <- list(no.shrink=1,prior.mean=0,prior.scale=1, prior.df=1,prior.no.shrink.mean=0,p
```

Note that the prior should be defined on the natural log scale for a log link GLM.

Value

a list of matrices containing the following components:

- `map`: matrix of MAP estimates, columns for coefficients and rows for features
- `sd`: matrix of posterior SD, same shape as `map`
- `prior.control`: list with details on the prior
- `fsr`: vector of the false sign rate for `coef`
- `svalue`: vector of the s-values for `coef`
- `interval`: matrix of either HPD or credible interval for `coef`
- `thresh`: vector of the posterior probability that the estimated parameter is smaller than the threshold value specified in `threshold` when MAP is positive (or greater than $-1 * \text{threshold}$ value when MAP is negative and `flip.sign` is `TRUE`)
- `diag`: matrix of diagnostics
- `contrast.map`: vector of MAP estimates corresponding to the contrast when contrast is given
- `contrast.sd`: vector of posterior SD corresponding to the contrast when contrast is given
- `ranges`: `GRanges` or `GRangesList` with the estimated coefficients, if `Y` was a `SummarizedExperiment`.

Note that all parameters associated with coefficients, e.g. `map`, `sd`, etc., are returned on the natural log scale for a log link GLM.

References

Adaptive Cauchy prior:

Zhu, A. (2018) Heavy-tailed prior distributions for sequence count data: removing the noise and preserving large differences. *Bioinformatics*. doi: 10.1093/bioinformatics/bty895

False sign rate and s-value:

Stephens, M. (2016) False discovery rates: a new deal. *Biostatistics*, 18:2. doi: 10.1093/biostatistics/kxw041

Examples

```
# Simulate RNA-Seq read counts data

# 5 samples for each of the two groups
# a total of 100 genes
n.per.group <- 5
n <- n.per.group * 2
m <- 100

# The design matrix includes one column of intercept
# and one column indicating samples that belong to the second group
condition <- factor(rep(letters[1:2], each = n.per.group))
x <- model.matrix(~condition)

# Specify the standard deviation of beta (LFC between groups)
beta.sd <- 2
beta.cond <- rnorm(m, 0, beta.sd)
beta.intercept <- runif(m, 2, 6)
beta.mat <- cbind(beta.intercept, beta.cond)

# Generate the read counts
mu <- exp(t(x %*% t(beta.mat)))
Y <- matrix(rnbinom(m*n, mu=mu, size=1/.1), ncol = n)

# Here we will use the negative binomial log likelihood
# which is an exported function. See 'logLikNB' for details.
# For the NB:
# 'param' is the dispersion estimate (1/size)
# 'offset' can be used to adjust for size factors (log of size factors)
param <- matrix(0.1, nrow = m, ncol = 1)
offset <- matrix(0, nrow = m, ncol = n)

# Shrinkage estimator of betas:
# (for adaptive shrinkage, 'apeglm' requires 'mle' coefficients
# estimated with another software, or by first running 'apeglm'
# setting 'no.shrink=TRUE'.)
res <- apeglm(Y = Y, x = x,
              log.lik = logLikNB,
              param = param,
              offset = offset,
              coef = 2)

head(res$map)
plot(beta.mat[,2], res$map[,2])
abline(0,1)
```

bbEstDisp

*Simple line-search estimator for dispersion of a beta binomial***Description**

Uses R's optimize function to find the maximum likelihood estimate of dispersion for a beta binomial distribution (theta for the dbetabinom function in the emdbook package). The counts, size, and beta are matrices, such that each row could be treated as a beta-binomial GLM problem.

Usage

```
bbEstDisp(success, size, weights = 1, x, beta, minDisp, maxDisp, se = FALSE)
```

Arguments

| | |
|---------|---|
| success | the observed successes (a matrix) |
| size | the total trials (a matrix) |
| weights | the weights (1 or a matrix) |
| x | the design matrix, as many rows as columns of success and size |
| beta | a matrix of MLE coefficients, as many rows as success and size |
| minDisp | the minimum dispersion value |
| maxDisp | the maximum dispersion value |
| se | logical, whether to return standard error estimate on the log of the dispersion (theta). Warning: the standard error estimates are not reliable at the boundary (log of minDisp and maxDisp), and should be interpreted with caution! |

Value

a vector of estimated dispersions (theta). if se=TRUE a matrix with columns: the vector of estimated dispersions and the standard errors for the log of the estimated dispersions

Examples

```
library(emdbook)
n <- 100
m <- 100
size <- matrix(rnbinom(n*m, mu=100, size=10), ncol=m)
success <- matrix(rbetabinom(n*m, prob=.5, size=size, theta=100), ncol=m)
x <- matrix(rep(1,m), ncol=1)
beta <- matrix(rep(0,n), ncol=1)
theta <- bbEstDisp(success=success, size=size, x=x, beta=beta, minDisp=1, maxDisp=500)
summary(theta)

# with standard error estimates on log of dispersion
fit <- bbEstDisp(success=success, size=size, x=x, beta=beta, minDisp=1, maxDisp=500, se=TRUE)
plot(fit[1:20,"theta"], ylim=c(0,500), ylab="theta-hat")
log.theta <- log(fit[1:20,"theta"])
log.theta.se <- fit[1:20,"se"]
segments(1:20, exp(log.theta - 2 * log.theta.se),
         1:20, exp(log.theta + 2 * log.theta.se))
abline(h=100,col="red")
```

`logLikNB`*Log likelihood for Negative Binomial*

Description

This is a simple function to be passed to `apeglm` as a log likelihood for the negative binomial distribution.

Usage

```
logLikNB(y, x, beta, param, offset)
```

Arguments

| | |
|---------------------|---|
| <code>y</code> | the counts |
| <code>x</code> | a design matrix |
| <code>beta</code> | the coefficient vector (natural log scale) |
| <code>param</code> | the overdispersion (alpha in DESeq2 notation) |
| <code>offset</code> | an offset matrix (natural log scale) |

Value

the log likelihood for each sample in `y`

Examples

```
# this function is used by 'apeglm' to specify
# a negative binomial log likelihood.
# so it's only passed as an argument, not for use on its own.
# we can show its output nevertheless:

y <- rnbinom(10, mu=100, size=1/.1)
x <- cbind(rep(1,10),rep(0:1,each=5))
beta <- c(log(100),0)
param <- .1
offset <- rep(0, 10)
logLikNB(y, x, beta, param, offset)
```

| | |
|--------|----------------------------|
| svalue | <i>Local FSR to svalue</i> |
|--------|----------------------------|

Description

Convert local FSR to svalue by taking the cumulative mean of increasing local FSRs. This is used within `apeg1m` to generate the svalue table, but provided as convenience function.

Usage

```
svalue(lfsr)
```

Arguments

`lfsr` the local false sign rates

Value

s-values

References

False sign rate and s-value:

Stephens, M. (2016) False discovery rates: a new deal. *Biostatistics*, 18:2. doi: 10.1093/biostatistics/kxw041

Examples

```
# Example 1 -- simulated local FSR data
local.fsr <- runif(1000)
sval <- svalue(local.fsr)

# Example 2 -- first runs example from 'apeglm'
example("apeglm")
local.fsr <- res$fsr[1, ]
sval <- svalue(local.fsr)
```


Index

`apeglm`, 2

`bbEstDisp`, 6

`logLikNB`, 7

`svalue`, 8