

Package ‘Neve2006’

November 14, 2024

Title expression and CGH data on breast cancer cell lines

Version 0.44.0

Author M. Neve et al. in Gray Lab at LBL

Description Experimental organization of combined expression and CGH data

Depends R (>= 2.14.0), tools, methods, utils, Biobase (>= 1.14.0),
hgu133a.db, annotate

Maintainer VJ Carey <stvjc@channing.harvard.edu>

License Artistic-2.0

LazyLoad yes

biocViews ExperimentData, CancerData, BreastCancerData

git_url <https://git.bioconductor.org/packages/Neve2006>

git_branch RELEASE_3_20

git_last_commit 5934bb3

git_last_commit_date 2024-10-29

Repository Bioconductor 3.20

Date/Publication 2024-11-14

Contents

cghExSet-class	1
logRatios	3
neveCGHmatch	4
Index	5

cghExSet-class	<i>Class "cghExSet" for combining CGH and expression data</i>
----------------	---

Description

combination of an ExpressionSet and CGH assay results

Usage

```
make_cghExSet(exprs, logRatios, cloneMeta, pd, mi, anno) # pd is AnnotatedDataFrame, mi is MIAME
```

Arguments

exprs	matrix of expression assay results
logRatios	matrix of aCGH assay results
cloneMeta	AnnotatedDataFrame for aCGH clone descriptions
pd	AnnotatedDataFrame for sample level data
mi	MIAME instance for experiment documentation
anno	character string with annotation platform descriptor for expression data

Objects from the Class

Objects can be created by calls of the form `new("cghExSet", phenoData, experimentData, annotation, exprs, logRatios, cloneMeta)`.

Slots

cghAssays: Object of class "AssayData" rectangular representation of logRatio data from CGH
cloneMeta: Object of class "AnnotatedDataFrame" information on chromosome and offset of clones
assayData: Object of class "AssayData" expression assay results
phenoData: Object of class "AnnotatedDataFrame" sample level data
featureData: Object of class "AnnotatedDataFrame" reporter level metadata for expression assay results
experimentData: Object of class "MIAME" container for experiment documentation
annotation: Object of class "character" identifiers for expression and CGH platforms, as a named vector with elements named 'exprs' and 'logRatios'
.__classVersion__: Object of class "Versions"

Extends

Class [eSet-class](#), directly. Class [VersionedBiobase-class](#), by class "eSet", distance 2. Class [Versioned-class](#), by class "eSet", distance 3.

Methods

cloneMeta signature(`cghSet = "cghExSet"`): extract annotated data frame on clone locations for CGH component
cloneNames signature(`cghSet = "cghExSet"`): extract character vector of clone IDs for CGH component
exprs signature(`object = "cghExSet"`): extract expression assay results
initialize signature(`.Object = "cghExSet"`): infrastructure
logRatios signature(`cghSet = "cghExSet"`): extract CGH assay results
show signature(`object = "cghExSet"`): display object in concise form
"[" signature(`object = "cghExSet"`): when first index is set, subset expression features; when second, subset samples

Author(s)

V Carey <stvjc@channing.harvard.edu>

References

R. M. Neve Cancer Cell Dec 2006

Examples

```
showClass("cghExSet")
data(neveExCGH)
logRatios(neveExCGH)[1:4,]
exprs(neveExCGH)[1:4,]
```

logRatios	<i>extractor for cghSet assay data</i>
-----------	--

Description

extractor for cghSet assay data

Usage

```
logRatios(cghSet)
```

Arguments

cghSet instance of [cghSet](#) class

Details

gets the AssayData element

Value

matrix

Author(s)

Vince Carey <stvjc@channing.harvard.edu>

Examples

```
data(neveCGHmatch)
logRatios(neveCGHmatch)[1:4,1:4]
```

`neveCGHmatch`*Neve Cancer Cell 2006 expression plus CGH data*

Description

ExpressionSet and cghSet

Usage

```
data(neveCGHmatch)
data(neveRMAMatch)
data(neveExCGH)
```

Format

The individual datasets (aCGH and expression assays) take the form of a cghSet for neveCGHmatch and an ExpressionSet for neveRMAMatch. There are only 50 samples because only 50 could be aligned on the given sample name tokens in the caArrayDB data as of June 9 2007. Those sample name tokens are very mangled in the CEL files.

The combined data structure neveExCGH has a special container class [cghExSet](#).

Source

links are provided in the pdf of the Cancer Cell paper; see the PMID of `experimentData(neveCGHmatch)`

References

PMID 17157791

Examples

```
data(neveCGHmatch)
neveCGHmatch
logRatios(neveCGHmatch)[1:4,1:4]
data(neveRMAMatch)
neveRMAMatch
```

Index

- * **classes**
 - cghExSet-class, 1
- * **datasets**
 - neveCGHmatch, 4
- * **models**
 - logRatios, 3
- [, cghExSet-method (cghExSet-class), 1
- cghExSet, 4
- cghExSet-class, 1
- cghSet, 3
- cghSet-class (logRatios), 3
- cloneMeta (cghExSet-class), 1
- cloneMeta, cghExSet-method (cghExSet-class), 1
- cloneNames (cghExSet-class), 1
- cloneNames, cghExSet-method (cghExSet-class), 1
- exprs, cghExSet-method (cghExSet-class), 1
- initialize, cghExSet-method (cghExSet-class), 1
- logRatios, 3
- logRatios, cghExSet-method (cghExSet-class), 1
- logRatios, cghSet-method (logRatios), 3
- make_cghExSet (cghExSet-class), 1
- MIAME, 2
- neveCGHmatch, 4
- neveExCGH (neveCGHmatch), 4
- neveRMAmatch (neveCGHmatch), 4
- show, cghExSet-method (cghExSet-class), 1